



INTRODUCING THE MARK II NEWCASTLE SAFE RANGE




The name Chubb is synonymous with security and has been for over 170 years. Chubb provides peace of mind in a world where there is an ever increasing incidence of theft/stealing each day. With effective security the risk and the loss can be minimised.

The Chubb Mark II Newcastle safe range has been improved over the previous model to meet the needs of those seeking a heavy duty commercial safe offering protection for moderate holdings of cash and valuables at an affordable

cost with fire protection for 90 minutes by test.

This competitively priced safe is designed to give resistance to oxy-acetylene, force, high speed drill and explosive attack. The body and door are filled with an improved barrier material.

As with all Chubb products you can feel secure with the knowledge that they are backed by Chubb's network providing complete after sales advice and 24 hour service throughout New Zealand and Australia.



In accordance with A2P regulation from CNPP of France Coffres Forts Classe 1 (Grade 1).



For fire-resistive containers in accordance with section 8.5 of JIS (Japan Industrial Standard) S1037 (1989) - 90 minute fire resistance.

SPECIFICATIONS: Mark II Newcastle Safe Range

■ **DOOR** - Overall thickness 145mm, with a defensive slab 75mm filled with Chubb F42 barrier material and additional protection over the locking area. Boltwork comprises 32mm moving bolts extending from 3 sides of the door. The hinge side is further protected by a full height dogging bar which engages into the body when the door is closed. Patent closures and a door seal ensure the safe will protect paper records from fire for up to 90 minutes. Lift off adjustable hinges are standard.

■ **LOCKING** - One three wheel keyless combination lock offering 1,000,000 variations and one six lever safe key lock are provided as standard. Both locks should always be used for enhanced security. One bolt down hole is provided.

■ **BODY** - Overall thickness 84mm, constructed from inner and outer steel body, enclosing Chubb F42 barrier material anchored to the body plates.

■ **FINISH** - A hard wearing and easy cleaning Chubb 'Warm Grey' polyurethane finish is standard. The protective fascia panel is finished in dark grey.



The handle and key lock escutcheon are finished in a harmonious dark brown. The combination dial is finished in an easy to read high lustre metallic silver.

■ **FIRE RATING** - Tested to provide 90 minutes fire protection for paper records. Sensitive materials such as stamps, microfilm, diskettes or magnetic media require extra fire protection and should be stored in a Chubb container designed for that purpose. Contact your nearest Chubb outlet for details.

■ **SERVICE** - For reliable operation, each 12 months the combination and keylocks should be cleaned and adjusted, and other door linkages inspected and cleaned to ensure their smooth operation. Contact your nearest Chubb authorised service outlet who will be able to arrange this service.

■ **BURGLARY ALARMS** - It is recommended that you fit as an option a Chubb vibration detector to the safe, connected into your alarm system. Any concerted physical attack will trigger the detector and raise the alarm.

■ **INSURANCE COVER** - The Chubb Mark II Newcastle safe has been designed to protect moderate cash risks. Some insurance companies have indicated a risk level of up to \$50,000 depending on circumstances. Please consult with your insurance company to determine the level of risk applicable to their requirements. Chubb produce a range of other safes designed for lower or higher risk situations, details of which are available from your nearest Chubb outlet.

DIMENSIONS - MODEL		NEWCASTLE	NEWCASTLE	NEWCASTLE	NEWCASTLE	NEWCASTLE
Millimetres		60	116	179	276	345
External	Height	628	718	1018	1208	1468
	Width	528	668	668	668	668
	Depth	603	663	663	773	773
	(see note below)					
Footprint -	Sq. Metres	.32	.44	.44	.52	.52
Internal	Height	460	550	850	1040	1300
	Width	360	500	500	500	500
	Depth	360	420	420	530	530
Volume (litres)		60	116	179	276	345
Depth req. to open door 90°		1076	1276	1276	1390	1390
Width req. to open door 180°		951	1230	1230	1230	1230
Weight kg's	Safe/Cased safe	360/405	500/580	670/740	995/1075	1160/1250
Lift capacity	(No of passengers)	6	8	10	15	17
Floor Loading - Kg/sq. metre		1131	1129	1513	1927	2246
	LB's/sq. Ft	187	187	250	319	371
Door locking points		4	5	6	6	9
Shelves adjustable included		1	1	2	3	4
Lockable drawers included		1(full width)	Pair	Pair	Pair	Pair
Nominal Drawer dimensions						
	Height	95	135	135	135	135
	Width	353	243 Each	243 Each	243 Each	243 Each

Note: External depth excludes door furniture. For overall depth including projections add 45mm.

Safe Division



Chubb Australia Limited

(A.C.N. 000 096 122)

149-155 Milton Street

Ashfield

N.S.W. 2131

Chubb New Zealand

76 Victoria Street

Wellington

Auckland

24 Burleigh Street

Phone (09) 377 0899

Fax (09) 377 6576

Palmerston North

20 The Square

Phone (06) 357 1434

Fax (06) 356 6334

Wellington

380 Jackson Street Petone

Phone (04) 568 5562

Fax (04) 568 4955

Christchurch

Cnr Manchester

& Kilmore Streets

Phone (03) 348 1420

Fax (03) 348 4916

Dunedin

5 Donald Street

Phone (03) 479 2301